

- High-volume axial blower 1,350 Cu. Ft./Min. (38.3 Cu. M/Min) provides an extra large swath width ensuring complete coverage.
- 2. 15-gallon (57 liter) lockable formulation tank. Translucent design allows for quick level viewing.
- 3. Large capacity formulation filter.
- 4. Water-resistant electronics enclosure features automatic calibration switch
- Super-accurate FMI pumping system features a lockable cover and Curtis Dyna-Fog's exclusive Formulation Anti-Pulsing System (FAPS™).
- **6.** Remote-control features: Tilt angle adjustment, machine on/off, spray on/off, formulation/flush selector, battery/hour meter (Backlit for night operation).



- **7.** Quick release stainless steel vehicle mounting brackets.
- **8.** High Speed Rotary Atomizer ensures 90% of the droplets produced will be below 20 micros at approved formulated label rates.
- 9. Patented articulating spray head powered via remote control.
- **10.** Water-resistant battery enclosure features chemical resistant stainless steel restraints.
- 11. 180° Rotational support (manually operated).
- 12. Light weight, 105 lbs. (47.6 kg).
- 13. High-strength anodized aluminum frame and stainless steel base construction. Chemical-resistant powder coated surfaces keeps the machine looking like new.
- 14. Anti-vibration mounting feet.

317.896.2561 www.dynafog.com